

DFR125R4WD20M

Produktnummer: 2456906

DFR125R4WD20M

Drill Fix DFR Bodies. Whistle Notch Shank. 4xD.

- Drill Fix DFR with rectangular-shaped inserts offer highest stability and feed rates at smaller sizes.
- X-offset design to adjust diameter size on turning machines and optimize tolerances on machining centers.
- Drill shipped with insert screws and Torx wrench.


Se vedlagt fil for spesifikasjoner eller [klikk her for å lese mer på leverandørens side >>](#)



Spesifikasjoner Kennametal

Vekt	0.246 kg
Bredde/tykkelse	0 mm
Høyde	0 mm
Volum	0.05 liter
Dimensjon	0
Nøkkelvidde	0 mm
kW	0
Innvendig diameter	0 mm
Utvendig diameter	0 mm
Type	KROPP
Type 4	0
Delelengde	0 mm
Type 3	0
Bredde ytre ring	0 mm
Bredde indre ring	0 mm
Type 2	0
Type 5	0
Bordiameter	12.5 mm
Bortype	DFR

Borelengde	4XD
Diameter	0 mm
Neseradius	0 mm
Lengde	0 mm
D5	27.0000
Pakke Størrelse	1
Beskrivelse	DRILL BODY DIAMETER=12.5-13.5 4XD
[D] Shank Diameter	20.0000
[L3] Brukende lengde	54.0000
LS	45.000,45.0000
LATTH	71.4800
D1 Maks	13.5000
[L] Total Lengde	117.0000
Skافت Type	Whistle Notch 2 CylindricalEnd
Platform	Drill Fix
[D1] Diameter	des.00
L4 Maks	50.0000
Varekode	DFR125R4WD20M
L2	45.0000
L1	72.0000
Maks omd.	B-Parallelogram 82
L5	0.5200



Les mer om produktet her:

<https://www.ail.no/product?number=2456906>