

DFR230R4WD32M

Produktnummer: 2457746

DFR230R4WD32M

Drill Fix DFR Bodies. Whistle Notch Shank. 4xD.

- Drill Fix DFR with rectangular-shaped inserts offer highest stability and feed rates at smaller sizes.
- X-offset design to adjust diameter size on turning machines and optimize tolerances on machining centers.
- Drill shipped with insert screws and Torx wrench.


Se vedlagt fil for spesifikasjoner eller [klikk her for å lese mer på leverandørens side >>](#)



Spesifikasjoner Kennametal

Vekt	0.559 kg
Bredde/tykkelse	0 mm
Høyde	0 mm
Volum	0.1 liter
Dimensjon	0
Nøkkelvidde	0 mm
kW	0
Innvendig diameter	0 mm
Utvendig diameter	0 mm
Type	KROPP
Type 4	0
Delelengde	0 mm
Type 3	0
Bredde ytre ring	0 mm
Bredde indre ring	0 mm
Type 2	0
Type 5	0
Bordiameter	23 mm
Bortype	DFR

Borelengde	4XD
Diameter	0 mm
Neseradius	0 mm
Lengde	0 mm
D5	42.0000
Pakke Størrelse	1
Beskrivelse	DRILL BODY DIAMETER=23.0-24.0 4XD
[D] Shank Diameter	32.0000
[L3] Brukende lengde	104.0000
LS	58.000,58.0000
LATTH	120.2400
D1 Maks	24.0000
[L] Total Lengde	179.0000
Skraft Type	Whistle Drive 2
Platform	Drill Fix
[D1] Diameter	23.0000
L4 Maks	92.0000
Varekode	DFR230R4WD32M
L2	58.0000
L1	121.0000
Maks omd.	B-Parallelogram 82
L5	0.7600



Les mer om produktet her:

<https://www.ail.no/product?number=2457746>