

UGDE0600A5ARA KC643M

Produktnummer: 4124324

UGDE0600A5ARAKC643M

Harvi II Long. UGDE. 3xD. Length of Cut.


- For finishing and semi-finishing applications.
- Unequal flute spacing minimizes chatter for smoother machining.
- Non-center cutting.
- Kennametal standard dimensions.



Spesifikasjoner Kennametal

Vekt	0.011468 kg
Bredde/tykkelse	0 mm
Høyde	0 mm
Volum	0.001 liter
Dimensjon	0
Nøkkelvidde	0 mm
Form	RADIE
kW	0
Tanning	5
Innvendig diameter	0 mm
Utvendig diameter	0 mm
Type	STANDARD FRES
Type 4	0
Lengde X dia	3XD
Delelengde	0 mm
Type 3	0
Serie	HARVI II
Kvalitet	KC643M
Bredde ytre ring	0 mm

Bredde indre ring	0 mm
Type 2	0
Type 5	0
Bordiameter	0 mm
Diameter	6 mm
Neseradius	0.2 mm
Arbeidsmateriale	Stål, Rustfritt stål, Støpejern, Superlegering, Herdet stål
Lengde	18 mm
Kvalitet	KC643M
Hjørnetype	Radius
D1	6.0000
Pakke Størrelse	1
Beskrivelse	HARVI II ENDMILL D=6 Z=5 R=0 2 LOC 3XD
[D] Shank Diameter	6.0000
[L3] Brukende lengde	18.0000
LS	42.0000
[L] Total Lengde	63.0000
Skaft Type	Straight-Cylindrical
Skaft Type	PLAIN
[Re] Radius	0.2000
Ap1 Maks	18.0000
Material Andre Grupper	Cast Iron
Platform	HARVI II
Material Hoved Grupper	Steel,Stainless Steel,High-Temp Alloys,Hardened Materials
[D1] Diameter	6.0000
Varekode	UGDE0600A5ARA
L2	63.0000,36.0000





Les mer om produktet her:

<https://www.ail.no/product?number=4124324>